

SP-RMT9



MODEL		SITTEN SP-RMT9
Part Number	POS2059	
EAN	5600865270034	
Type	Portable direct thermal printing	
SPECIFICATIONS		
Printing speed	43 lines/seg Max 90mm/seg Average: 60mm/seg	
Printing length	72mm	
Type of cut	Manual	
Resolution	576 dots/line (8 dots/mm)	
Interfaces	Bluetooth, USB	
Sensors	Out of paper warning Almost out of paper warning	
Sleep mode	Yes	
Buzzer	Yes	
Compatibility	Windows / Linux / Android	
Emulations	ESC / POS	
Other functions	Energy saving mode; Standby mode; Automatic reset	
PRINTING FONTS		
Fonts	OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/OEMWest Europe/Greek Hebrew / East European / Iran / WPC1252 / OEM866 / OEM852 7 OEM858 / Iran II Latvian / Arabic / PT1511251 / OEM747 / WPC1257 / Vietnam / OEM864 / Hebrew / WPC1255 / Thai	
Barcodes	1D:UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE1282D: PDF417, QR code, DATA Matrix	
PAPER		
Type of paper	Thermal paper	
Size	79mm +/- 0.5mm	
Paper thickness	0.06 up to 0.08mm	
Diameter of the roll	Máx. 40mm	
Printing length	72mm	
Feeding paper method	Drop-in	
RELIABILITY		
Head lifetime	50Km	
MCBF	100.000.000 lines	
OTHER		
Dimensions (LxWxH)	103x99x46mm (printer) 213x1551x88 (box)	
Weight	256g (printer) 745g (with box)	
Running temperature	Standby: -20°C~60°C Running: 0°C~50°C	
Humidity	10~90%	
Battery	Rechargeable lithium battery 7.4V / 1.5Ah Standby up to 3/4 days	
Power supply	DC 9V/2A	
Certification	CE FCC MIC ROHS	