

BT-882i



MODEL		SITTEN BT-882i
Part number		POS2133
EAN		-
Type		Mobile Thermal Printer
SPECIFICATIONS		
Printing mode		Thermal printing
Printing speed		70mm/seg
Printing width		72mm
Cutting type		Manual
Resolution		203dpi (8dot/mm)
NV flash buffer		256Kb
Input buffer		128Kb
Interfaces		Bluetooth, USB, RS232
Sensors		Out of paper light Open cover light
Compatibility		iOS / Windows / Android
Emulations		ESC / POS
Other functions		Saving energy mode, stand-by mode and automatic reset
PRINTING FONTS		
Fonts		OEM437 / Katakana / OEM850 / OEM860 / OEM863 / OEM865 / WEST EUROPE / GREEK / HEBREW / EAST EUROPE / IRAN PC1252 / OEM866 / OEM852 / OEM858 / IRAN II / LATVIAN / ARABIC / PT(S1125) / OEM747 / WPC1257 VIETNAM / OEM864 / HEBREW / WPC1255 / THAI
Barcode		UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128/QR Code
PAPER		
Type of paper		Thermal paper
Size		80mm +/-0.5mm
Roll diameter		Máx. 40mm
RELIABILITY		
Head lifetime		100Km
MCBF		100.000.000 lines
OTHER		
Dimensions (LxWxH)		100x45x115mm (printer) 207x115x65mm (box)
Weight		260g (printer) 570g (with box)
Operating temperature		Standby: -20°C~60°C Running: 0°C~50°C
Humidity		10~90%
Battery		Lithium rechargeable battery Standby up to 3/4 days
Power supply		7.4V / 2Ah (2000mAh)
Certification		CE FCC MIC ROHS